LABDEX

Automatic Decapping Centrifuge
LX201ADC

Email: info@labdex.com **website:** www.labdex.com

Description

Automatic Decapping Centrifuge LX201ADC is an automated table top centrifuge with a speed range of 4000 rpm for efficient vacuum blood collection tubes of size 75 mm and 100 mm. Built-in feature for automated calculation of RCF value. Electronic interlock protects the unit from unwanted interruptions during the operation. It is specially designed for clinics, hospitals, blood bank, radioimmunoassay, etc.

Specifications

Maximum speed	4000 rpm
Maximum RCF	3030 x g
Maximum capacity	80 tube (ϕ13x75/100mm tubes)
Speed accuracy	± 10 rpm
Timer range	1 s to 99 min59 s
Noise	≤65dB(A)
Power	700 W
Power supply	AC220V ±22V 50Hz
Dimensions (H x W x D)	470 x 560 x 380 mm
Weight	50 kg
Packing dimension (W x D x H)	800 x 600 x 600 mm
Gross weight	84 kg

Features

- LCD display for visual monitoring of speed and RCF
- Automated calculation of RCF values
- In-built damping set for vibration release
- Electronic interlock safety
- Equipped with microprocessor control system with variable frequency AC blushless motor
- Vacuum blood collection tube is automatically capped with more than 90%, convenient and quick
- Multiple self-defined programs can be saved

Applications

- Used in blood bank, hospital, research lab and other fields for separation of blood components.

Rotor Selection

Rotor name	Maximum speed (rpm)	Maximum capacity (ml)	Maximum RCF (×g)
Swing rotor	4000	80 tube (ϕ13x75/100mm)	3030

71-75 Shelton Street Covent Garden, London WC2H 9JQ UK.

Email: info@labdex.com | Website: www.labdex.com